

**G 20/3.15A/F****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

For protection against overcurrent, we offer cartridge fuse with dimensions 5x20 mm in sizes from 100 mA to 6.3 A.

**General ordering data**

Version	Miniature fuse, quick-acting, 3.15 A, G-Si. 5 x 20
Order No.	<a href="#">0431100000</a>
Type	G 20/3.15A/F
GTIN (EAN)	4008190012977
Qty.	10 pc(s).

## G 20/3.15A/F

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	5 mm	Depth (inches)	0.197 inch
Height	20 mm	Height (inches)	0.787 inch
Width	5 mm	Width (inches)	0.197 inch
Net weight	1.08 g		

## Material data

Colour	Light Grey
--------	------------

## System specifications

Version	Fuse accessories
---------	------------------

## Fuse cartridges

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	3.15 A
Melting integral	4 A <sup>2</sup> s	Optical function display	No
Power output (@ 1.5 In)	2.2 W	Rated breaking capacity	1.5 kA
Version	Fuse accessories	Voltage drop	220 mV

## Rating data

Rated voltage	250 V	Rated current	3.15 A
---------------	-------	---------------	--------

## Classifications

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ETIM 8.0	EC002704	ETIM 9.0	EC002704
ECLASS 9.0	27-14-20-01	ECLASS 9.1	27-14-20-01
ECLASS 10.0	27-14-20-01	ECLASS 11.0	27-14-20-01
ECLASS 12.0	27-14-20-01	ECLASS 13.0	27-14-20-01
ECLASS 14.0	27-14-20-01		

## Environmental Product Compliance

REACH SVHC	/
RoHS Compliance Status	Compliant without exemption

## Approvals

ROHS	Conform
------	---------

## Downloads

User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	