

# Product Datasheet

## Characteristic

# 10206

Micro Pragma surface enclosure -  
IP30 - 1x4modules - reversible  
transparent door



### Main

|                                 |                           |
|---------------------------------|---------------------------|
| Range                           | Micro Pragma              |
| product or component type       | Enclosure                 |
| Enclosure type                  | Modular enclosure         |
| Number of 18 mm modules per row | 4                         |
| Number of horizontal rows       | 1                         |
| type of front cover             | Reversible<br>Transparent |
| Width                           | 88 mm                     |
| Height                          | 130 mm                    |
| Depth                           | 60 mm                     |

### Complementary

|                               |  |
|-------------------------------|--|
| enclosure mounting            | Surface                                |
| 9 mm pitches                  | 8                                      |
| Total number of 18 mm modules | 4                                      |
| Type of rail                  | DIN                                    |
| Mounting plate description    | Without mounting plate                 |
| Enclosure material            | Enclosure: self-extinguishing material |
| Internal depth                | 54 mm                                  |
| Colour                        | Enclosure: white (RAL 9003)            |
| Market segment                | Small commercial                       |

### Environment

|                         |  |
|-------------------------|--|
| Standards               | EN 60439-3<br>IEC 23-48<br>IEC 60695-2-1<br>IEC 60439-3                  |
| Fire resistance         | 650 °C ( 30 s ) conforming to IEC 60695-2-1                              |
| IP degree of protection | IP40 conforming to IEC 60529 (with installation of devices IP40 minimum) |
| IK degree of protection | IK07 conforming to EN 50102  |

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

|                              |            |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 6.000 cm   |
| Package 1 Width              | 8.500 cm   |
| Package 1 Length             | 13.000 cm  |
| Package 1 Weight             | 96.000 g   |
| Unit Type of Package 2       | S04        |
| Number of Units in Package 2 | 60         |
| Package 2 Height             | 30.000 cm  |
| Package 2 Width              | 40.000 cm  |
| Package 2 Length             | 60.000 cm  |
| Package 2 Weight             | 6.358 kg   |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 240        |
| Package 3 Height             | 45.000 cm  |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 37.432 kg  |

### Offer Sustainability

|                             |   |
|-----------------------------|---|
| REACH Regulation            | Reference contains Substances of Very High Concern above the threshold      |
| EU RoHS Directive           | Pro-active compliance (Product out of EU RoHS legal scope)                  |
| Mercury free                | Yes   |
| China RoHS Regulation       | Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information  | Yes   |
| Halogen content performance | Halogen free product  |