

## Technical data sheet

Article number:  
111-04891

T50R



<b>Product Group</b>	Cable ties for higher impact resistant polyamide 6.6 ScanBlack
<b>Product Family</b>	T-Series in PA66HIR(S)
<b>Material</b>	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
<b>Bundle Diameter max (metric)</b>	50.0 mm
<b>Bundle Ø min.</b>	1.5 mm
<b>Flammability</b>	UL 94 HB
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	200 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +80 °C
<b>Releasable Closure (Yes/No)</b>	No
<b>Thickness (T)</b>	1.2 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.0013 kg
<b>Width (W)</b>	4.6 mm

HF ✓ RoHS ✓