

WPD 100 2X25/6X10 GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Potential distributor terminal, Screw connection, Light Grey, 25 mm², 101 A, 1000 V, Number of levels: 1, V-0, Wemid
Order No.	1561910000
Type	WPD 100 2X25/6X10 GY
GTIN (EAN)	4050118367218
Qty.	3 pc(s).

WPD 100 2X25/6X10 GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	49 mm	Depth (inches)	1.929 inch
Height	55.4 mm	Height (inches)	2.181 inch
Width	30.2 mm	Width (inches)	1.189 inch
Net weight	102 g		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	130 °C		

Material data

Material	Wemid	Colour	Light Grey
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection	End cover plate required	No
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	Yes	PE connection	No
N-function	No	PE function	No
PEN function	No		

Additional technical data

Explosion-tested version	Yes	Installation advice	Terminal rail / mounting plate
Open sides	closed	Type of mounting	Snap-on

Conductors for clamping (additional connection)

Connection type, additional connection Screw connection

Conductors for clamping (rated connection)

Connection direction	on side	Type of connection	Screw connection
----------------------	---------	--------------------	------------------

General

Installation advice	Terminal rail / mounting plate	Number of poles	1
Standards	IEC 60998-2-1		

Rating data

Rated cross-section	25 mm ²	Rated voltage	1,000 V
Rated AC voltage	1,000 V	Rated DC voltage	1,000 V
Rated current	101 A	Standards	IEC 60998-2-1

WPD 100 2X25/6X10 GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ETIM 9.0	EC000897
ECLASS 9.0	27-14-11-20	ECLASS 9.1	27-14-11-20
ECLASS 10.0	27-14-11-20	ECLASS 11.0	27-14-11-20
ECLASS 12.0	27-14-11-20	ECLASS 13.0	27-25-01-19
ECLASS 14.0	27-25-01-19		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	9b5f0838-1f0b-4c14-9fc7-3f5e6ee75be2
RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c

Approvals

Approvals



ROHS


Conform

Downloads

Approval/Certificate/Document of Conformity	CB Certificate FIMKO certificate VDE Certificate DNV Certificate CE Declaration of Conformity UKCA declaration of conformity Confirmation of Standards EN 45545-2_2020-10
Engineering Data	CAD data – STEP
User Documentation	StorageConditionsTerminalBlocks DATA SHEET WPD 100 Manual - How to connect aluminum wires in WPD-Terminal blocks
Catalogues	Catalogues in PDF-format
Brochures	

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings



Conductor connection data according to DIN EN 60900-1, IEC 61213-2 (Data A+Cu+Al)											
Conductor (mm²)		Copper		Aluminum		Straps (mm²)		Copper		Aluminum	
2x25	25	1.250	1.250	1.250	1.250	6x16	16	1.250	1.250	1.250	1.250
2x35	35	1.500	1.500	1.500	1.500	6x25	25	1.500	1.500	1.500	1.500
2x50	50	1.750	1.750	1.750	1.750	6x35	35	1.750	1.750	1.750	1.750
2x70	70	2.000	2.000	2.000	2.000	6x50	50	2.000	2.000	2.000	2.000
2x95	95	2.250	2.250	2.250	2.250	6x70	70	2.250	2.250	2.250	2.250
2x120	120	2.500	2.500	2.500	2.500	6x95	95	2.500	2.500	2.500	2.500
2x150	150	2.750	2.750	2.750	2.750	6x120	120	2.750	2.750	2.750	2.750
2x185	185	3.000	3.000	3.000	3.000	6x150	150	3.000	3.000	3.000	3.000
2x240	240	3.500	3.500	3.500	3.500	6x240	240	3.500	3.500	3.500	3.500
2x300	300	4.000	4.000	4.000	4.000	6x300	300	4.000	4.000	4.000	4.000
2x400	400	4.500	4.500	4.500	4.500	6x400	400	4.500	4.500	4.500	4.500
2x500	500	5.000	5.000	5.000	5.000	6x500	500	5.000	5.000	5.000	5.000
2x630	630	5.500	5.500	5.500	5.500	6x630	630	5.500	5.500	5.500	5.500
2x800	800	6.000	6.000	6.000	6.000	6x800	800	6.000	6.000	6.000	6.000
2x1000	1000	6.500	6.500	6.500	6.500	6x1000	1000	6.500	6.500	6.500	6.500
Stripping length		12 mm				Stripping length		9 mm			
code		MS (+/- R2)				code		MS (+/- R2)			
Straight		Fold		Flexible with braid							

