

WS 10/5 MC NE WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text.

WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | |
|--------------------|---|
| Version | WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, Allen-Bradley, white |
| Order No. | 1635000000 |
| Type | WS 10/5 MC NE WS |
| GTIN (EAN) | 4008190261948 |
| Qty. | 720 pc(s). |
| compatible printer | 2715590000 2438520000 2438510000 |

WS 10/5 MC NE WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Height | 10 mm | Height (inches) | 0.394 inch |
| Width | 5 mm | Width (inches) | 0.197 inch |
| Net weight | 0.136 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

General data

| | | | |
|--------------------------------------|-------------------------------|-----------|--|
| Application/manufacture | Weidmueller, Allen-Bradley | | |
| Colour | white | | |
| Colour of printing | black | | |
| Halogen | No | | |
| Material | Polyamide 66 | | |
| Number of markers per combination | 1 MultiCard = Terminal marker | | |
| Number of markers per packaging unit | Form of supply | MultiCard | |
| Operating temperature range | -40...100 °C | | |
| Operating temperature range, max. | 100 °C | | |
| Operating temperature range, min. | -40 °C | | |
| Printed characters | neutral | | |
| UL 94 flammability rating | V-2 | | |
| Width | 5 mm | | |

Connector markers

| | |
|-----------------|------|
| Pitch in mm (P) | 5 mm |
|-----------------|------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| ETIM 8.0 | EC000761 | ETIM 9.0 | EC000761 |
| ECLASS 9.0 | 27-14-11-37 | ECLASS 9.1 | 27-14-11-37 |
| ECLASS 10.0 | 27-14-11-37 | ECLASS 11.0 | 27-28-11-01 |
| ECLASS 12.0 | 27-28-11-01 | ECLASS 13.0 | 27-28-11-01 |
| ECLASS 14.0 | 27-28-11-01 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| REACH SVHC | / |
| RoHS Compliance Status | Compliant without exemption |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

WS 10/5 MC NE WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

| | |
|-----------------------------|--|
| Engineering Data | CAD data – 20900_WS_10-5_MC_DXF.dxf CAD data – STEP |
| Engineering Data | Zuken E3.S |
| Product Change Notification | Technical change to MultiCard material - DE Technical change to MultiCard material - EN MultiCard Material modification MultiCard Material Modifikation |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

Data sheet

WS 10/5 MC NE WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings



Drawing

