

## WKM 8/20

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



The halogen-free, transparent pocket of the WKM offers outstanding protection against environmental influences. Thanks to firm fixation with cable ties, it is suitable for almost all wire cross-sections.

The pre-printed tags are simply inserted into the WKM holder and secured with a clip. WKM cable markers are the right solution for maximum efficiency in on-site marking.

Your advantage when using WKM cables

- Paper and polyester labels can be printed individually with conventional office printers
- The robust design in combination with MultiCard ELS tags guarantees maximum protection against environmental influences

### General ordering data

|            |  |
|------------|--|
| Version    | WKM, Conductor and cable markers, 7 - 115 mm, 20 x 8 mm, Wire and cable markers, Transparent |
| Order No.  | <a href="#">1753490000</a>   |
| Type       | WKM 8/20   |
| GTIN (EAN) | 4032248010615  |
| Qty.       | 50 pc(s).  |

## WKM 8/20

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 3.5 mm  | Depth (inches)  | 0.138 inch |
| Height     | 20 mm   | Height (inches) | 0.787 inch |
| Width      | 8 mm    | Width (inches)  | 0.315 inch |
| Net weight | 0.457 g |                 |            |

## Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...80 °C |
|-----------------------------|-------------|

## General data

|                                      |   |           |  |
|--------------------------------------|---|-----------|--|
| Application/manufacture              | Wire and cable markers                    |           |  |
| Colour                               | Transparent                               |           |  |
| Material                             | Polypropylene                             |           |  |
| Number of markers per combination    | 1 MultiCard = Conductor and cable markers |           |  |
| Number of markers per packaging unit | Form of supply                            | MultiCard |  |
| Operating temperature range          | -40...80 °C                               |           |  |
| Operating temperature range, max.    | 80 °C                                     |           |  |
| Operating temperature range, min.    | -40 °C                                    |           |  |
| Type of printing                     | neutral                                   |           |  |
| UL 94 flammability rating            | HB  |           |  |
| Width                                | 8 mm                                      |           |  |

## Conductor and cable markers

|                               |                    |                                  |                          |
|-------------------------------|--------------------|----------------------------------|--------------------------|
| Conductor O.D.                | 7 - 115 mm         | Conductor O.D., max.             | 115 mm                   |
| Conductor O.D., min.          | 7 mm               | Conductor cross-section, max.    | 150 mm <sup>2</sup>      |
| Conductor cross-section, min. | 16 mm <sup>2</sup> | Cross-section for connected wire | 16 - 150 mm <sup>2</sup> |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| REACH SVHC             | /                           |
| RoHS Compliance Status | Compliant without exemption |

## Important note

|                     |  |
|---------------------|--|
| Product information | For cable ties with a width up to 7.7 mm |
|---------------------|--|

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Data sheet**

**WKM 8/20**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**

**Downloads**

---

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |

---

**WKM 8/20**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Example of use**

