

SAIB-M8-3P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

General ordering data

| Version | Field attachable connector, M8, Female socket, straight |
|------------|---|
| Order No. | <u>1803870000</u> |
| Туре | SAIB-M8-3P |
| GTIN (EAN) | 4032248259854 |
| Qty. | 1 pc(s). |



SAIB-M8-3P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

| Net weight | 10 a |
|------------|------|

Technical data customisable plug-in connectors

| Cable diameter | 3.55 mm |
|-------------------------------|---------------------|
| Cable diameter, min. | 3.5 mm |
| Conductor cross-section, max. | 0.5 mm ² |
| Contact surface | Gold-plated |
| Insulation strength | $10^{8} \Omega$ |
| Plugging cycles | ≥ 50 |
| Protection degree | IP67 |
| Rated voltage | 60 V |
| Temperature range of housing | -40 +85 ° C |
| Type of connection | Screw connection |
| | |

| Cable diameter, max. | 5 mm |
|-------------------------------|----------------------|
| Coding | none |
| Conductor cross-section, min. | 0.14 mm ² |
| Housing main material | PA |
| Number of poles | 3 |
| Pollution severity | 3 |
| Rated current | 4 A |
| Shield connection | No |
| Threaded ring material | Diecast zinc |
| | |

Classifications

| ETIM 6.0 | EC002635 |
|-------------|-------------|
| ETIM 8.0 | EC002635 |
| ECLASS 9.0 | 27-44-01-02 |
| ECLASS 10.0 | 27-44-01-02 |
| ECLASS 12.0 | 27-44-01-16 |
| ECLASS 14.0 | 27-44-01-16 |

| ETIM 7.0 | EC002635 |
|-------------|-------------|
| ETIM 9.0 | EC002635 |
| ECLASS 9.1 | 27-44-01-03 |
| ECLASS 11.0 | 27-44-01-02 |
| ECLASS 13.0 | 27-44-01-02 |
| | |

Environmental Product Compliance

| REACH SVHC | Lead 7439-92-1 |
|------------------------|--------------------------------------|
| SCIP | ebf89fc8-a87f-4691-b87a-dfb9921774b4 |
| RoHS Compliance Status | Compliant |

Approvals

Approvals



| ROHS | Conform |
|-------------------------|------------|
| UL File Number Search | UL Website |
| Certificate no. (cULus) | E307231 |

Downloads

| Engineering Data | CAD data – STEP |
|--------------------|-------------------------------------|
| Engineering Data | Zuken E3.S |
| User Documentation | <u>Manual</u> |
| Catalogues | Catalogues in PDF-format |
| Brochures | FL FIELDWIRING EN FL FIELDWIRING EN |