

# Product Datasheet

## Characteristic

# 19071

Auxiliary double OC contact, Acti9  
NG125, 2 OC, 220VAC to 240VAC (max  
6A), 415VAC (max 3A)



### Main

Range	Acti9
product or component type	Double OC contact
Device short name	OF and OF
Signal contacts composition	2 C/O
[In] rated current	0.1...3 A at 415 V, AC 50/60 Hz 0.1...6 A at <= 240 V, AC 50/60 Hz 0.1...1 A at 130 V, DC 0.1...3 A at <= 48 V, DC
9 mm pitches	1

### Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
mounting mode	Fixed
mounting support	DIN rail
Height	102.8 mm
Width	15.3 mm
Depth	75.5 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal1 cable(s) 0.5...2.5 mm <sup>2</sup> - rigid Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible with ferrule Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - rigid Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - flexible Plate terminal2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
Product certifications	LCIE ASEFA KEMA ASTA
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1

Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	7.4 cm
Package 1 Length	10.2 cm
Package 1 Weight	65 g
Unit Type of Package 2	BB1
Number of Units in Package 2	9
Package 2 Height	12 cm
Package 2 Width	9 cm
Package 2 Length	24 cm
Package 2 Weight	649 g
Unit Type of Package 3	S03
Number of Units in Package 3	81
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.337 kg

## Offer Sustainability

REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	&nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins