



PRODUCT-DETAILS

# OTP25T3M

## OTP25T3M Safety switch



### General Information

Extended Product Type	OTP25T3M
Product ID	1SCA022401R0090
EAN	6417019130859
Catalog Description	OTP25T3M Safety switch

**Long Description**

Safety switch, 3-p. 415V AC23 30A, 15kW. Mounted auxiliary contact: 1NO0NC. Plastic enclosure. IP65. Black Selector handle. Interlocked cover. Defeatable interlocking. The enclosure in the OTP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal.

### Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201

RoHS Information	1SCC340075D0201
RoHS Status	Following EU Directive 2011/65/EU
SCIP	5efcadc1-89b3-4a5c-a288-c0a724aea88d Finland (FI)
Simplified SCIP	e5a67717-0620-4a6e-9db0-5754704ed8b4 Germany (DE) 8c3aa446-5513-43a6-99f6-55a308592801 Norway (NO) 21d328db-872b-42f2-9574-f12af749a801 Poland (PL) 0b06cee8-9c4b-46df-b944-51e79dd429fc Bulgaria (BG) 4f7aa09d-f846-48df-b6d1-9ae75ea0c593 Sweden (SE) 69549d6a-03f7-4742-8abf-2d4f9fbd3c80 Portugal (PT) 28640300-0629-46da-af3a-a4737469b280 Greece (GR) f3c0cfe7-e094-488e-a2d6-1622cb4ef53c Estonia (EE) fd748fc7-cef8-46ba-8254-f8bf407dd813 Hungary (HU) e11a5f47-b162-4f74-8f6f-6bf3ec04b0a7 Hungary (HU) 7f63d021-eb09-4983-a2d8-346f17f8c0e5 Belgium (BE) e83e3683-134a-4156-a6e2-8f4898c5345b Spain (ES) 2e44f71f-d5ec-4dd4-a530-8ad5b512e5a3 France (FR) c721897e-7f82-404f-a119-7ffeaa81ab6c Sweden (SE) c2fb2131-f673-4a59-ae0b-7aff826b0a52 Czech Republic (CZ) 023818d5-1e6e-480d-8486-b247d29d0b6e Croatia (HR) 9331ce28-c204-4855-b43d-1b1b7aea169d France (FR) 01ee26bd-4982-4e9c-b806-4533b7873d76 Denmark (DK) 0bb6a9dd-1a4f-417c-ae10-d0f06cf0fee5 Germany (DE) 0e6048ed-b8b6-47c8-b27f-c549f011bf5d Germany (DE) 476884fe-9b89-4a96-b5c5-40e10635604e Germany (DE) e26fbebba-a959-4e43-b4be-5cf7109d50ba Poland (PL) 794b1df0-3529-4531-82b8-36d0462027d2 Belgium (BE) 297d2cbb-fbc6-4d7b-9b84-26c39b4bbc5e Netherlands (NL) fad2b7b6-db57-49c8-a030-5ebfe32345be Poland (PL) ecd1541f-4377-40cc-a81e-5ae2d7a6e196 Italy (IT) 4bd6b576-cb34-408c-a361-8a55144c7812 Germany (DE)
Toxic Substances Control Act - TSCA	1SCC340095D0201

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340002M0012
Mechanical Drawings	OTPK201490SM32.stp

### Dimensions

Product Net Width	145 mm
Product Net Height	200 mm
Product Net Depth / Length	90 mm
Product Net Weight	0.8 kg

### Technical

Rated Operational Current AC-22A (I <sub>e</sub> )	(380 ... 415 V) 45 A (500 V) 45 A (690 V) 45 A
--	--

Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 30 A (500 V) 30 A (690 V) 20 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 15 kW (500 V) 15 kW (690 V) 15 kW
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V AC) 1.4 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 1 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	13 kA
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Pollution Degree	3
Handle Color	Black
Handle Type	Selector handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	3
Neutral Type	Fixed neutral
Connecting Capacity Main Circuit	Screw Clamp 1.5 ... 35 mm <sup>2</sup> Screw Clamp / PE Terminal 2pc, 1.5 ... 35 mm <sup>2</sup>
Cable Cross-Section	1.5 ... 35 mm <sup>2</sup>
Wire Stripping Length	13 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Cable Entry Position	Top and/or Bottom
Cable Outlets Per Side	2xM32+M16 / 2xM32+M16
Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK08
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	1 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Tightening Torque	Main Circuit 2 N·m

### Technical UL/CSA

Wire Stripping Length	13 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Tightening Torque	Main Circuit 2 N·m

---

### Certificates and Declarations

---

BV Certificate	1SCC340018D0204
Declaration of Conformity - CE	1SCC340003D2704
DNV GL Certificate	1SCC340045D0203

---



---

### Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	162 mm
Package Level 1 Depth / Length	222 mm
Package Level 1 Height	148 mm
Package Level 1 Gross Weight	0.9 kg
Package Level 1 EAN	6417019130859

---



---

### Classifications

---

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122205
IDEA Granular Category Code (IGCC)	5166 >> Safety switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3642254
E-Number (Norway)	1428952
E-Number (Sweden)	3140152

---



---

### Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

