



PRODUCT-DETAILS

# OT40M3

## OT40M3 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT40M3
Product ID	1SCA022497R0490
EAN	6417019158402
Catalog Description	OT40M3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted, DIN-rail mountable switch-diconnector with protected clamp terminals, handle and shaft are not included, suitable for distribution board with 45mm slots

Eco Transparency	
Environmental Product Declaration - EPD	1SCC301278D0201

Environmental	
Environmental Information	1SCC301262D0201

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301052M0006
Environmental Product Declaration - EPD	1SCC301278D0201

Dimensions	
Product Net Width	35 mm
Product Net Height	68 mm
Product Net Depth / Length	73 mm
Product Net Weight	0.09 kg

Technical	
Rated Operational Current AC-21A (I <sub>e</sub> )	(380 ... 415 V) 40 A
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(220 ... 240 V) 5.5 kW (400 ... 415 V) 11 kW (500 V) 11 kW (690 V) 11 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	Θ = 40 °C 40 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 40 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Rated Insulation Voltage	acc. to IEC/EN 60664-1 750 V

(U<sub>i</sub>)

Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> )	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 0.5 kA
Rated Conditional Short-Circuit Current (I <sub>nc</sub> )	(40 A fuse, ≤415V) 50 kA (25 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 1.6 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	Cu 0.75 ... 10 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

## Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 0.8 N·m
-------------------	--------------------------

## Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301166D2703
UL Certificate	No certification needed
VDE Certificate	No certification needed

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	86 mm
Package Level 1 Depth / Length	103 mm
Package Level 1 Height	82 mm
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	6417019158402

Classifications		
Object Classification Code		Q
ETIM 8	EC000216 - Switch disconnecter	
ETIM 9	EC000216 - Switch disconnecter (low voltage)	
UNSPSC		39122233
eClass		V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Finland)		3601203
E-Number (Sweden)		2102720

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

