



PRODUCT-DETAILS

OT40F4C

OT40F4C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT40F4C
Product ID	1SCA104934R1001
EAN	6417019390741
Catalog Description	OT40F4C CHANGE-OVER SWITCH
Long Description	40A Manual Change-Over Switch, Handle and shaft need to be ordered separately, Open transition

Eco Transparency	
Environmental Product Declaration - EPD	1SCC301272D0201

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201

RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301054M0006
Environmental Product Declaration - EPD	1SCC301272D0201

Dimensions

Product Net Width	96 mm 3.78 in
Product Net Height	68 mm 2.68 in
Product Net Depth / Length	68 mm 2.68 in
Product Net Weight	0.27 kg 0.6 lb

Technical

Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A
Rated Operational Power AC-23A (P _e)	(380 ... 415 V) 11 kW (500 V) 11 kW (690 V) 11 kW
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 40 A
Conventional Thermal Current (I _{the})	Fully Enclosed 40 A
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 0.5 kiloampere rms

Power Loss	at Rated Operating Conditions per Pole 1.6 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	0.75 ... 10 mm ²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Transition Type	Open

Technical UL/CSA

Ampere Rating	40 A
Horsepower Rating UL/CSA	(acc. to UL 200 V) 10 Hp (acc. to UL 208 V) 10 Hp (acc. to UL 240 V) 10 Hp (acc. to UL 480 V) 20 Hp (acc. to UL 600 V) 25 Hp
Tightening Torque	acc. IEC 60947-1 0.8 N·m

Certificates and Declarations

Declaration of Conformity - CE	1SCC303019D2702
DNV Certificate	1SCC303138D0201

Container Information

Package Level 1 Units	box 1 box
Package Level 1 Width	80 mm 3.15 in
Package Level 1 Depth / Length	108 mm 4.25 in
Package Level 1 Height	79 mm 3.11 in
Package Level 1 Gross Weight	0.31 kg 0.70 lb
Package Level 1 EAN	6417019390741

Classifications

Object Classification Code	Q
----------------------------	---

ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601443

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

