



PRODUCT-DETAILS

# OT30FT3

## OT30FT3 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT30FT3
Product ID	1SCA105074R1001
EAN	6417019392042
Catalog Description	OT30FT3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, door mounted, switch-diconnector / non-fusible diconnect switch with front protected clamp terminals, handle and shaft are not included

Eco Transparency	
Environmental Product Declaration - EPD	1SCC301280D0201

Environmental	
Environmental Information	1SCC301183D0201

Material Compliance		
Conflict Minerals Reporting Template (CMRT)		9AKK108467A5658
REACH Declaration		1SCC011021D0201
RoHS Information		1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Toxic Substances Control Act - TSCA		1SCC011025D0201

Ordering		
Minimum Order Quantity		1 piece
Customs Tariff Number		85365080
Country of Origin		Finland (FI)

Popular Downloads		
Data Sheet, Technical Information		1SCC301020C0201
Instructions and Manuals		1SCC301057M0007
Mechanical Drawings		1SCC301470F0001 1SCC301469F0001 OT125FT3.igs
Environmental Product Declaration - EPD		1SCC301280D0201

Dimensions		
Product Net Width		70 mm
Product Net Height		100 mm
Product Net Depth / Length		66.5 mm
Product Net Weight		0.42 kg

Technical		
Rated Operational Current AC-21A (I <sub>e</sub> )		(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A (I <sub>e</sub> )		(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I <sub>e</sub> )		(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Power AC-23A (P <sub>e</sub> )		(380 ... 415 V) 18.5 kW (500 V) 22 kW (690 V) 37 kW
Rated Impulse Withstand Voltage (U <sub>imp</sub> )		8 kV
Rated Insulation Voltage (U <sub>i</sub> )		acc. to IEC/EN 60664-1 750 V
Rated Operational		Main Circuit 750 V

Voltage	
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 3.6 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(125 A fuse, 415 V) 50 kA (125 A fuse, 690 V) 10 kA (63 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 0.7 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Special Functions	No
Mounting Type	Door mounting
Number of Poles	3
Connecting Capacity Main Circuit	Flexible 1x Cu 2.5...25 mm <sup>2</sup> Stranded 1x Cu 2.5...25 mm <sup>2</sup>
Cable Cross-Section	Cu 2.5 ... 25 mm <sup>2</sup>
Wire Stripping Length	Main Circuit 17-18 mm
Recommended Screw Driver	Main Circuit Hexagon 4
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 6.2 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	30 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 30 Hp
Wire Stripping Length	Main Circuit 17-18 mm
Recommended Screw Driver	Main Circuit Hexagon 4
Tightening Torque	acc. IEC 60947-1 6.2 N·m

Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301010D0201
UL Certificate	cULus certificate OT30-125

VDE Certificate

No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	71 mm
Package Level 1 Height	76 mm
Package Level 1 Gross Weight	0.44 kg
Package Level 1 EAN	6417019392042

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	3171943

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

