



---

**PRODUCT-DETAILS****OT160G03P****OT160G03P SWITCH-DISCONNECTOR**

---

**General Information**

Extended Product Type	OT160G03P
Product ID	1SCA135139R1001
EAN	6417019638706
Catalog Description	OT160G03P SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted switch-diconductor with protected clamp terminals and with black IP65 handle and shaft

---

**Circular Value**

End of Life Instructions	1SCC301116M0201
--------------------------	-----------------

---

**Eco Transparency**

Environmental Product Declaration - EPD	1SCC301281D0201
---	-----------------

**Environmental**

Environmental Information	1SCC301267D0201
---------------------------	-----------------

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	6f064110-8ade-4356-9916-63b327acc3b7 Finland (FI)
Simplified SCIP	9695ceac-9a5e-47a3-9d10-913be99f61f2 Germany (DE) 8765d64a-1254-4740-b28b-ffd01ce6515e Sweden (SE) 3681be30-0ecc-4559-922c-3b97a79d0da4 Poland (PL) b55c5251-02d9-435f-90e2-96ddf56b519 Poland (PL) 092dd1c4-c806-46a2-bd5d-4041c5776f1e France (FR) e4ad0e9c-310a-4370-b58a-e9061e6a7bc7 Estonia (EE) 12544bfd-5174-4e17-a112-be5ff151b3e8 Bulgaria (BG) b2d74db4-ac58-4226-97f5-54e578e3be08 Greece (GR) d6258643-2026-405c-a2d4-f58707d1ac46 Croatia (HR) f6ed35dc-cfbc-4783-a265-c5cf8d8cd88b Portugal (PT) 0d3525da-aa66-47e6-9cd9-cc463adeb861 Sweden (SE) 32dc2de6-cd6e-400c-88f3-7907ffe5f316 Hungary (HU) 00a80986-0c31-4117-879b-c97b5019ae7b Czech Republic (CZ) 5ba42181-654d-465d-ad59-eef68bc47e09 Netherlands (NL) 1bde6823-5682-419b-a3ff-cd201dea689d Germany (DE) 798c0614-8d5c-4122-82af-01d963ea7f64 Germany (DE) ce70bfa1-b9e0-4ae5-9535-37b4eaf61b49 Belgium (BE) 825bde5b-85ec-4c5d-8cf5-5abe0b98f0fa Norway (NO) 7d786ffd-c696-4ea2-9940-de8c6b33c784 Germany (DE) df72ae17-3e35-4c10-8169-240c0fae359d Poland (PL) e6f961a8-7c4e-4a38-91d9-7da31e97aeab Denmark (DK) 17fa4b90-0c59-4330-8af1-2fecb845eab4 Germany (DE) ad47b5c2-dead-418f-97d2-d1004114861f Italy (IT) 7a3eb990-9440-4f07-a1ff-711db106a55c Spain (ES) b8605eb2-93cc-4a46-8a90-f39401d925eb Belgium (BE) 6be34c1d-5dd5-49ea-8e37-e833145c84af France (FR) e328478e-18e3-4cda-b415-18eaef621254 Hungary (HU)
Toxic Substances Control Act - TSCA	1SCC011025D0201

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

**Popular Downloads**

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301089M0204
Mechanical Drawings	OT160G3_model.igs
Environmental Product Declaration - EPD	1SCC301281D0201
End of Life Instructions	1SCC301116M0201

## Dimensions

Product Net Width	123 mm
Product Net Height	130 mm
Product Net Depth / Length	73 mm
Product Net Weight	0.9 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 45 kW (400 ... 415 V) 75 kW (500 V) 90 kW (690 V) 132 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 160 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 160 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 12 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 4 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(200 A fuse, 500 V) 100 kA (200 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front and side operated
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	Cu 10 ... 70 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals

Tightening Torque	acc. IEC 60947-1 6 N·m
Mechanical Durability	20000
Lock Type	Yes

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	125 A
Horsepower Rating UL/CSA	(240 V AC) Single Phase 20 Hp (440 ... 480 V AC) Single Phase 30 Hp
Tightening Torque	acc. IEC 60947-1 6 N·m
Tightening Torque UL/CSA	53 in·lb

## Certificates and Declarations

A2L Certificate – IEC	1SCC301336D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301210D2701
DNV GL Certificate	1SCC301174D0204
UL Certificate	cULus certificate OT160G
VDE Certificate	No certification needed

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	160 mm 6.3 in
Package Level 1 Depth / Length	244 mm 9.6 in
Package Level 1 Height	96 mm 3.8 in
Package Level 1 Gross Weight	1 kg 2.3 lb
Package Level 1 EAN	6417019638706

## Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3638769
E-Number (Sweden)	3171058

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

