

**SFX 9/24 MM WS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Highly flexible: SFX**

SFX markers are the preferred choice for labelling cables if you prefer the classic cable tie solution. Cables do not always run in a straight line. The material used in SFX markers addresses this fact with highly flexible polyurethane. The marker follows each curve of the cable and latches on with ease.

**General ordering data**

|                    |  |
|--------------------|--|
| Version            | SlimFix, Conductor and cable markers, 7 -, 26 x 15 mm, white |
| Order No.          | <a href="#">2005320000</a>                                   |
| Type               | SFX 9/24 MM WS   |
| GTIN (EAN)         | 4050118390254  |
| Qty.               | 1,000 pc(s).   |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a>        |

## SFX 9/24 MM WS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 0.6 mm  | Depth (inches)  | 0.024 inch |
| Height     | 26 mm   | Height (inches) | 1.024 inch |
| Width      | 15 mm   | Width (inches)  | 0.591 inch |
| Net weight | 0.255 g |                 |            |

## Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...90 °C |
|-----------------------------|-------------|

## General data

|                                   |              |                                   |              |
|-----------------------------------|--------------|-----------------------------------|--------------|
| Colour                            | white        | Halogen                           | No           |
| Material                          | Polyurethane | Number per roll                   | 1,000        |
| Operating temperature range       | -40...90 °C  | Operating temperature range, max. | 90 °C        |
| Operating temperature range, min. | -40 °C       | Size of labelling field           | 23.5 x 9 mm  |
| UL 94 flammability rating         | HB           | Version                           | halogen-free |
| Width                             | 15 mm        |                                   |              |

## Conductor and cable markers

|                      |         |                   |         |
|----------------------|---------|-------------------|---------|
| Cable tie passage    | Flat    | Conductor O.D.    | 7 -     |
| Conductor O.D., min. | 7 mm    | Halogen           | No      |
| Suitable cable tie   | Plastic | Text field height | 23.5 mm |
| Text field width     | 9 mm    |                   |         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | /                           |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |

**Data sheet**

**SFX 9/24 MM WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)


**Drawings**



**SFX 9/24 MM WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Accessories****THM MULTIMARK**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | MULTIMARK ROLLER 115       |
| Order No.  | <a href="#">1357420000</a> |
| GTIN (EAN) | 4050118160314              |
| Qty.       | 1 pc(s).                   |

**Ink ribbons**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.


**General ordering data**

|            |                            |            |
|------------|----------------------------|------------|
| Type       | RIBBON MM 76/360 SW        | Version    |
| Order No.  | <a href="#">2005080000</a> | Ink ribbon |
| GTIN (EAN) | 4050118389951              |            |
| Qty.       | 1 pc(s).                   |            |

**Data sheet****SFX 9/24 MM WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Accessories****THM MULTIMARK PLUS**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                             |
|------------|-----------------------------|
| Type       | MULTIMARK PLUS ROLLER 1 ... |
| Order No.  | <a href="#">2672590000</a>  |
| GTIN (EAN) | 4050118708097               |
| Qty.       | 1 pc(s).                    |