

**CD 60X40 4/6 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

The broad range of cable ducts offers you a flexible wire management system in a constant quality. The accurately sizes of the punched holes in accordance to DIN EN 50085-2-3 enables you a precise installation. Next to wire holding lugs as fixing aid for already installed wires, the optimal closing mechanism provide an easy snapping as well as a safe fit of the lid.

**General ordering data**

|            |                                                       |
|------------|-------------------------------------------------------|
| Version    | Cable duct, 60 mm x 40 mm, 4.00 mm x 6.00 mm, 2000 mm |
| Order No.  | <a href="#">2589230000</a>                            |
| Type       | CD 60X40 4/6 GY                                       |
| GTIN (EAN) | 4050118603064                                         |
| Qty.       | 36 m                                                  |

## CD 60X40 4/6 GY

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

## Dimensions and weights

|            |           |                 |            |
|------------|-----------|-----------------|------------|
| Height     | 60 mm     | Height (inches) | 2.362 inch |
| Width      | 40 mm     | Width (inches)  | 1.575 inch |
| Length     | 2,000 mm  | Length (inches) | 78.74 inch |
| Net weight | 402.778 g |                 |            |

## Temperatures

|                             |            |
|-----------------------------|------------|
| Operating temperature range | -5...60 °C |
|-----------------------------|------------|

## General information

|                           |                                 |                             |                                         |
|---------------------------|---------------------------------|-----------------------------|-----------------------------------------|
| Colour                    | grey                            | Flexible wiring duct        | No                                      |
| Halogen                   | Yes                             | Included in delivery        | Cable duct, Lid                         |
| Lid                       | Yes                             | Material                    | PVC / lead-free                         |
| Non-tracking              | Yes                             | Operating temperature range | -5...60 °C                              |
| Slit gap                  | 6 mm                            | Slit width                  | 4 mm                                    |
| Standards                 | In accordance with DIN EN 50085 | Type of mounting            | when screwed in, With adhesive, Riveted |
| UL 94 flammability rating | V-0                             | Usable cross-section        | 1,960 mm <sup>2</sup>                   |
| Version of side panel     | slotted                         |                             |                                         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000012    | ETIM 7.0    | EC000012    |
| ETIM 8.0    | EC000012    | ETIM 9.0    | EC000012    |
| ECLASS 9.1  | 27-40-07-03 | ECLASS 10.0 | 27-40-07-03 |
| ECLASS 11.0 | 27-40-07-03 | ECLASS 12.0 | 27-40-07-03 |
| ECLASS 13.0 | 27-40-07-03 | ECLASS 14.0 | 27-40-07-03 |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| REACH SVHC             | /                           |
| RoHS Compliance Status | Compliant without exemption |

## Approvals

Approvals



|                       |            |
|-----------------------|------------|
| ROHS                  | Conform    |
| UL File Number Search | UL Website |
| Certificate No. (UR)  | E500004    |

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|

## CD 60X40 4/6 GY

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

