



PRODUCT-DETAILS

# SHD203/16

## SHD203/16 Switch Disconnectors



General Information	
Extended Product Type	SHD203/16
Product ID	2CDD273111R0016
EAN	4016779904421
Catalog Description	SHD203/16 Switch Disconnectors
Long Description	SHD203/16 - Switch Disconnector 3P, 16A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 40.8 %
Principles Recyclability Rate	
Group Waste to Landfill Target	
No non-hazardous waste is sent to a landfill	

Offered with Extended Lifetime	Product Durability
Offered with Takeback Services	Take Back for Recycling
End of Life Instructions	9AKK108469A1171

Technical

Rated Voltage (U <sub>r</sub> )	415 V 12 V Minimum
Rated Operational Voltage	415 V AC
Operational Voltage	Maximum 436 V AC Minimum 12 V AC
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Input Voltage Type	AC
Rated Current (I <sub>n</sub> )	16 A
Rated Conditional Short-Circuit Current (I <sub>nc</sub> )	10 kA
Rated Frequency (f)	50 / 60 Hz
Power Loss	at Rated Operating Conditions per Pole 1.01 W
Electrical Endurance	20000 AC cycle
Mechanical Endurance	20000 cycle
Number of Contacts CO	0
Number of Contacts NC	0
Number of Contacts NO	3
Number of Poles	3
Overvoltage Category	III
Tightening Torque	2 N·m
Utilization Category	Switching of mixed resistive and inductive loads, including moderate overloads - frequent actuation (AC-22A)
Actuator Type	Toggle
Screw Terminal Type	Cable Clamp
Switch Type	Off
Actuator Marking	I / O
Actuator Material	Insulation Group II, Red, Sealable
Housing Material	Insulation Group I, RAL 7035
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Accessories Available	No
Cover Color	Grey
Connecting Capacity	Flexible 0.75 ... 16 mm <sup>2</sup> Rigid 0.75 ... 25 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup>
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	2CDK440035D2703
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20210528
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contain substances > 0.1 mass percentage

REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms

Dimensions

Width in Number of Modular Spacings	3.0
Product Net Width	52.5 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.225 kg
Built-In Depth (t2)	69 mm

Ordering

Package Level 1 Units	1 piece
Package Level 1 Gross Weight	0.24 kg

Certificates and Declarations

Declaration of Conformity - CE	2CDK440035D2703
--------------------------------	-----------------

Installation

Instructions and Manuals	2CDC441016D0201
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CDC441016D0201
-----------------------------------	-----------------

Classifications

ETIM 8	EC001545 - Main switch for distribution board
ETIM 9	EC001545 - Main switch for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 90 95
eClass	V11.0 : 27142301
Object Classification Code	Q

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Switch Disconnectors  
Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)

