

PRODUCT-DETAILS

# C11 110-301 C11 110-301, Energy meter'Steel', None, Singlephase, 5 A



General Information	
Extended Product Type	C11 110-301
Product ID	2CMA103572R1000
EAN	7392696035729
Catalog Description	C11 110-301, Energy meter'Steel', None, Single-phase, 5 A
Long Description	Basic compact meters for use in residential applications for single or multi family houses or in stand alone applications. To be used in a four wire system. The meter has instrumentation values. Single phase direct connected for active energy. One output for pulses or alarm etc.  Accuracy class 1.0 (or B for MID meters). The meters is IEC approved. 1000 imp/kWh.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A4138

Technical	
Function	Electricity meter
Sub-Function Sub-Function	Steel
Rated Voltage (U <sub>r</sub> )	230 V

C11 110-301 2/4

Voltage Range	184264 V
Rated Current (I <sub>n</sub> )	5 A
· · · · · · · · · · · · · · · · · · ·	Maximum 40 A
Current Rating	5 A
Rated Frequency (f)	50 / 60 Hz
	0.22 W
Power Loss	0.22 W
Communication Interface	None
Accuracy	Active Energy Class ±0.5%
Measuring Instrument Conformity	IEC 62053-22
Meter Tariff Rating	One-Tariff One-Tariff
Pulse Output Rate	1000
Number of Poles	1
Number of Phases	Single-phase
Number of Counter Positions	6
Number of Digital In/Outputs	1 DO
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass and terminal cover. Glass reinforced polycarbonate in housing.
I/O Option	1 digital output
Material Compliance	2010/10000
RoHS Information	2CMC486003
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	2011-44
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	
Ambient Air Temperature	Operation -25 70 °C
Degree of Protection	IP20
Environmental Information	2CMC486005D0001
Dimensions	
Width in Number of Modular Spacings	1
Product Net Width	17.5 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.066 kg
Dimension Diagram	2CMC486001M0201

C11 110-301 3/4

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	98 g
E-Number (Finland)	6701063

#### Certificates and Declarations

Declaration of Conformity 2CMC486001D0001

#### Installation

Instructions and Manuals 2CMC486006M0201

#### Popular Downloads

Data Sheet, Technical 2CMC486001M0201 Information

## Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283011
eClass	V11.0 : 27142316
Object Classification Code	<u>P</u>

### Accessories

710000001100				
Identifier	Description	Туре	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1, Energy Management	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1, Energy Management	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

#### Categories

C11 110-301 4/4

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Energy\ Efficiency\ Devices \rightarrow Energy\ Meters$ 





