



PRODUCT-DETAILS

LBAS375TPN

LBAS375TPN Safety switch



General Information	
Extended Product Type	LBAS375TPN
Product ID	2CMA142628R1000
EAN	7392696426282
Catalog Description	LBAS375TPN Safety switch
Long Description	Safety switch, 3-p. 415V AC23 75A, 37kW. Mounted auxiliary contact: 1NO0NC. Aluminium enclosure. IP65. Black Round handle. Interlocked cover. The dye casted aluminum alloy (silumin) enclosure is extremely rigid, and well suited for harsh environment. The surface is polyester coated and well protected from corrosion. Installation is made easy, thanks to the easy access to terminals, screwed cover and with the grommet type of glands included (IP54). The cover is interlocked, and handle padlockable with two padlocks. The handle can also be padlocked in On position, by removing two small plastic bits. N and PE terminals included.

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201

RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Bulgaria (BG)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340166M0205
Mechanical Drawings	OTFK2231614RM40.stp

Dimensions

Product Net Width	160 mm
Product Net Height	230 mm
Product Net Depth / Length	118 mm
Product Net Weight	1.75 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 80 A (500 V) 80 A (690 V) 80 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 75 A (500 V) 58 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 37 kW (500 V) 37 kW (690 V) 18.5 kW
Conventional Free-air Thermal Current (I_{th})	80 A
Conventional Thermal Current (I_{the})	Fully Enclosed 80 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 2.1 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 1.5 kA
Handle Color	Black
Handle Type	Round handle
Standards	IEC 60947-1, -3
Number of Poles	3
Neutral Type	Fixed neutral
Connecting Capacity	Screw Clamp 1.5 ... 35 mm ²

Main Circuit	Screw Clamp / PE Terminal 1pc,6 ... 35 mm²
Cable Cross-Section	1.5 ... 35 mm²
Wire Stripping Length	13 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Cable Entry Position	Top and/or Bottom
Cable Outlets Per Side	2xM40 / 2xM40+M16
Impact Resistance Rating	Housing IK09
Enclosure Material	Aluminium
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	1 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Tightening Torque	Main Circuit 2 N·m
Rated Current (I _N)	75 A

Technical UL/CSA

Wire Stripping Length	13 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Tightening Torque	Main Circuit 2 N·m

Certificates and Declarations

Declaration of Conformity - CE	1SCC340062D2702
--------------------------------	-----------------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm
Package Level 1 Depth / Length	240 mm
Package Level 1 Height	150 mm
Package Level 1 Gross Weight	1.75 kg
Package Level 1 EAN	7392696426282

Classifications

Object Classification Code	Q 2CMT005069
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122205
IDEA Granular Category Code (IGCC)	5166 >> Safety switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

