



PRODUCT-DETAILS

FH202 AC-63/0.03

FH202 AC-63/0.03 Residual Current Circuit Breaker 2P Type AC 30 mA



General Information	
Extended Product Type	FH202 AC-63/0.03
Product ID	2CSF202004R1630
EAN	8012542893806
Catalog Description	FH202 AC-63/0.03 Residual Current Circuit Breaker 2P Type AC 30 mA
Long Description	The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications.

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 48 %
Principles Recyclability Rate	
Sustainable Material	0 %

Content

Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	Recycled Paper - 78 %
Improved Resource Efficiency for Customers	Digital Efficiency - Product is digitally-supported to optimize usage and eventually optimize customer asset
Offered with Extended Lifetime	Product Durability
End of Life Instructions	9AKK108469A2269

Eco Transparency

Environmental Product Declaration - EPD	9AKK108467A3700
---	-----------------

Technical

Standards	IEC/EN 61008
Type of Residual Current	Type AC
Rated Voltage (U_r)	230 V
Rated Operational Voltage	230 V
Rated Insulation Voltage (U_i)	500 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Rated Current (I_n)	63 A
Rated Residual Current	30 mA
Rated Conditional Short-Circuit Current (I_{nc})	10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	1 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Rated Frequency (f)	50 Hz
Power Loss	at Rated Operating Conditions per Pole 3.2 W
Number of Poles	2
Operating Characteristic	Instantaneous
Mounting Type	DIN-Rail
Options Provided	None
Accessories Available	No
Rated Cross-Section	4 - Multi-Wired 10...25 mm ² 1 - Solid-Core 25...25 mm ²

Material Compliance

RoHS Information	9AKK106713A5603
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

Environmental

Ambient Air Temperature	Operation -5 ... +40 °C Storage -40 ... +70 °C
Degree of Protection	IP2X
Environmental Information	Refer to RoHS

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 A
--	--------

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	69 mm
Product Net Depth / Length	85 mm
Product Net Weight	0.2 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.236 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5603
-----------------------------------	-----------------

Installation

Instructions and Manuals	No document needed
-----------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CSC400030D0202
--------------------------------------	-----------------

Classifications

ETIM 8	EC000003 - Residual current circuit breaker (RCCB)
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142201
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs

