

PRODUCT-DETAILS

AU60.10FR AU60.10FR Mounting box Red IP3X



General Information	
Extended Product Type	AU60.10FR
Product ID	2TKA00004281
EAN	6438199008172
Catalog Description	AU60.10FR Mounting box Red IP3X
Long Description	AU60.10FR is installation box which is certified to be used in EI60 and EI30 fire rated walls. The mounting box includes a rotating, steplessly adjustable extension ring enabling installation on boards with a thickness of 12-40mm. Screw distance is c/c 60mm. The green adapter ring, delivered with the box, is used in single-board walls (12 -13 mm). The ring is removed when the wall thickness is two boards (24-26 mm). In case of triple boards, extension ring is lifted to needed height. The box has two fixed inlets, both of them are open (other sealed with a plug) and both inlets are equipped with a locking device in metal for reliable connection between the conduits and the box. Both flexipipe and stiff/rigid conduits can be connected to the inlets and both inlets have 16/20 mm piping adapters. The extension ring can be tilted 0-4. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

Environmental Product

© 2024 ABB. All rights reserved.

9AKK108469A2312

Subject to change without notice

2024/10/28

Technical	
Application	Fire protection
Model Number	Single
Number of Conduit Inlets	6
Number of Gangs	1
Number of Inlet Inserts Included	2
Design	Device connection box (round/square)
Cover Mounting Type	Snap On
Mounting Type	Flush-mounted (plaster)
Switching Equipment Mounting Type	Screw
Shape	Round
Surface Finishing	Untreated
Material	Plastic, Thermoplastic
Includes	None
Cover Style	Construction Protective Cover
Color	Red
Number of Batteries	0

Material Compliance	
RoHS Information	9AKK106713A4634
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20240314
REACH Declaration	9AKK106713A4633
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240314
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Degree of Protection	IP3X

Dimensions	
Product Net Width	0.071 m
Product Net Height	0.057 m
Product Net Depth / Length	0.071 m
Product Net Weight	0.08765 kg

Ordering	
Package Level 1 Units	box 50 piece
Package Level 1 Gross Weight	0.428 kg

© 2024 ABB. All rights reserved.

E-Number (Finland)	1152361
E-Number (Norway)	1220012
E-Number (Sweden)	142056:
Certificates and Declarations	
Declaration of Conformity - CE	9AKK108467A7115
Installation	
Instructions and Manuals	No document needed
Popular Downloads Data Sheet, Technical	No document needed
Information	
Building Information Modeling – BIM	9AKK108468A3693
Classifications	
ETIM 8	EC002601 - Box/housing for built-in mounting in the wall/ceiling
ETIM 9	EC002601 - Box/housing for built-in mounting in the wall/ceiling
WEEE Category	Product Not in WEEE Scope
CN8	39259080
Safety Information	
Circuit Integrity	E 60

Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Installation Materials} \rightarrow \text{Flush Mounted Boxes} \rightarrow \text{Fire Resistant Boxes} \rightarrow \text{Hollow Wall}$



2024/10/28

Subject to change without notice