20EAKS 1/3



PRODUCT-DETAILS

20EAKS

Socket outlet Without imprint White



General Information	
Extended Product Type	20EAKS
Product ID	2TKA000660G1
EAN	6410024061316
Catalog Description	Socket outlet Without imprint White
Long Description	There are terminals for each contact of the socket outlet. The terminals are for max 2 rigid wires.
Installation Instructions and Manuals	9AKK10103A3029
	9AKK10103A3029 Surface mounted (plaster)
Instructions and Manuals	
Instructions and Manuals Mounting Type	Surface mounted (plaster)

2/3 20EAKS

Technical	
Data Sheet, Technical Information	9AKK10103A302
Number of Phases	
Number of Active Pin Terminals	
Number of Gangs	
Connection Type	Push-l
Socket Outlet Type	Protective Contact (SCHUKC
Number of Batteries	
Electrical	
Rated Voltage (U _r)	250
Rated Current (I _n)	16,7
Frequency (f)	50 50 H
Design	
Surface Finishing	Untreate Gloss
Material	Plastic, Thermoplasti
Legend	Without imprir
Label Space Provided	N
RAL Number	RAL 9010 - Pure Whit
Color	Whit
Dimensions	
Product Net Width	63 mr
Product Net Height	43 mr
Product Net Depth / Length	63 mr
Product Net Weight	0.075 k
Material Compliance	
RoHS Information	9AKK106713A463
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
REACH Declaration	9AKK106713A463
REACH Information REACH Date	False - does not contain substances > 0.1 mass percentag 2024031
Conflict Minerals Reporting Template (CMRT)	9AKK108468A336
Certificates and Declarations	
Declaration of Conformity	9AKK108468A673
- CE	3ARK 100400A073
Classifications	
ETIM 9	EC000125 - Socket outle
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
© 2024 ABB. All rights reserved.	2024/09/05 Subject to char

20EAKS 3/3

WEEE B2C / B2B Business To Consumer

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Surface\ Mounted\ Range \rightarrow Socket\ Outlets$

