



PRODUCT-DETAILS

AN20

AN20 Inlet M20



General Information	
Extended Product Type	AN20
Product ID	2TKA160025G1
EAN	6410011527573
Catalog Description	AN20 Inlet M20
Long Description	Inlet AN20 is equipped with locking device which prevents conduit disconnection. The conduit can be unfastened by twisting it. The inlet can be used both in mounting boxes and in junction boxes. Made of halogen free material (IEC/61249-2-21).

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108469A3874

Material Compliance	
RoHS Information	9AKK106713A4634
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20240314

REACH Declaration	9AKK106713A4633
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240314
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Product Net Width	0.028 m
Product Net Height	0.038 m
Product Net Depth / Length	0.026 m
Product Net Weight	0.0051 kg

Ordering

Package Level 1 Units	box 100 piece
Package Level 1 Gross Weight	0.51 kg
E-Number (Finland)	1152757
E-Number (Sweden)	1422343

Certificates and Declarations

Declaration of Conformity - CE	9AKK108467A7115 9AKK108468A1342
--------------------------------	------------------------------------

Installation

Instructions and Manuals	9AKK10103A2549
--------------------------	----------------

Popular Downloads

Data Sheet, Technical Information	9AKK10103A2549
Building Information Modeling – BIM	9AKK108468A3684

Classifications

ETIM 8	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
ETIM 9	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Installation Materials → Flush Mounted Boxes → Accessories for Plastic Flush Mounted Boxes → Inlets

