

# Product Datasheet

## Characteristic

# A9F75232

Miniature circuit breaker (MCB), Acti9 iC60N, 2P, 32A, D curve, 6000A (IEC/EN 60898-1), 10kA (IEC/EN 60947-2)



## Main

|                           |   |
|---------------------------|---|
| Device application        | Distribution  |
| Range                     | Acti9   |
| Product name              | Acti9 iC60  |
| product or component type | Miniature circuit-breaker   |
| Device short name         | IC60N   |
| poles description         | 2P  |
| Number of protected poles | 2   |
| [In] rated current        | 32 A  |
| Network type              | AC<br>DC  |
| Trip unit technology      | Thermal-magnetic  |
| Curve code                | D   |
| Breaking capacity         | 6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>36 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 kA Icu at <= 125 V DC conforming to EN/IEC 60947-2<br>10 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>20 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>6 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>36 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Utilisation category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2   |
| Suitability for isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2  |
| Standards                 | IEC 60947-2<br>IEC 60898-1<br>EN 60898-1<br>EN 60947-2  |

## Complementary

|                                       |   |
|---------------------------------------|---|
| Network frequency                     | 50/60 Hz  |
| Magnetic tripping limit               | 12 x In +/- 20 %  |
| [Ics] rated service breaking capacity | 15 kA 75 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 75 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 kA 75 % conforming to EN 60947-2 - 440 V AC 50/60 Hz |

|  |   |
|--|---|
|  | 15 kA 75 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 75 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 kA 75 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>27 kA 75 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz<br>27 kA 75 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz<br>6000 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz<br>6000 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz<br>10 kA 100 % conforming to IEC 60947-2 - 72...125 V DC<br>10 kA 100 % conforming to EN 60947-2 - 72...125 V DC |
| [Ui] rated insulation voltage                    | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2   |
| [Uimp] rated impulse withstand voltage           | 6 kV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2   |
| Contact position indicator                       | Yes   |
| Control type                                     | Toggle  |
| local signalling                                 | Trip indicator  |
| mounting mode                                    | Fixed   |
| mounting support                                 | DIN rail  |
| Comb busbar and distribution block compatibility | Top or bottom: YES  |
| 9 mm pitches                                     | 4   |
| Height   | 85 mm   |
| Width  | 36 mm   |
| Depth  | 78.5 mm   |
| net weight                                       | 0.25 kg   |
| Colour   | White   |
| Mechanical durability                            | 20000 cycles  |
| Electrical durability                            | 10000 cycles  |
| Connections - terminals                          | Single terminal (top or bottom) 1...35 mm <sup>2</sup> rigid<br>Single terminal (top or bottom) 1...25 mm <sup>2</sup> flexible   |
| Wire stripping length                            | 14 mm for top or bottom connection  |
| Tightening torque                                | 3.5 N.m top or bottom   |
| Earth-leakage protection                         | Separate block  |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP20 conforming to EN 60529 |
| Pollution degree                      | 3 conforming to EN 60947-2<br>3 conforming to IEC 60947-2   |
| Overvoltage category                  | IV  |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                 |
| Relative humidity                     | 95 % at 55 °C   |
| Operating altitude                    | 0...2000 m  |
| Ambient air temperature for operation | -35...70 °C   |
| Ambient air temperature for storage   | -40...85 °C   |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 7.5 cm   |
| Package 1 Width              | 3.6 cm   |
| Package 1 Length             | 9.5 cm   |
| Package 1 Weight             | 245 g    |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 6        |
| Package 2 Height             | 8 cm     |
| Package 2 Width              | 9.8 cm   |
| Package 2 Length             | 22.5 cm  |
| Package 2 Weight             | 1.532 kg |
| Unit Type of Package 3       | S03      |

|                              |           |
|------------------------------|-----------|
| Number of Units in Package 3 | 66        |
| Package 3 Height             | 30 cm     |
| Package 3 Width              | 30 cm     |
| Package 3 Length             | 40 cm     |
| Package 3 Weight             | 17.337 kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | Reference contains Substances of Very High Concern above the threshold  |
| EU RoHS Directive          | Compliant with Exemptions   |
| China RoHS Regulation      | Product out of China RoHS scope. Substance declaration for your information   |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | ENVPEP1705002EN   |
| Circularity Profile        | N/A   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |