Product Datasheet

Kerren Citi Committee Comm

Characteristic

A9XAH657

Acti9 - comb busbar - 3L balanced wtih Aux - 18 mm pitch - 57 modules



Main

Range	Acti9	
product or component type	Comb busbar	
mounting mode	Horizontal	
Accessory / separate part categor	Connection accessory	
Lines description	3L + N	
Total number of 18 mm modules	57	

Complementary

38 ways Aux + N + L
1 x 1P
18 mm
Tooth
27 mm
L1 L2 L3
Insulated
Cuttable
Set of 10 end piece
100 A at 40 °C
415 V AC
500 V AC conforming to IEC 61439-2
Top or bottom on tunnel type terminals Top or bottom on double terminal
114
1000 mm
White (RAL 9003)
Acti 9 Acti9 iC60 Acti 9 Acti9 iK60 Acti 9 Acti9 iID Acti 9 Acti9 iID K Acti 9 Acti9 iSW Acti 9 Acti9 iSW-NA Multi9 Multi9 C60

Environment

Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.520 cm
Package 1 Width	0.900 cm
Package 1 Length	106.000 cm
Package 1 Weight	525.000 g
Unit Type of Package 2	P12
Number of Units in Package 2	135
Package 2 Height	50.000 cm
Package 2 Width	120.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	88.572 kg

Offer Sustainability

orier odotamability	
Sustainable offer status	Green Premium product
REACh Regulation	Free of Substances of Very High Concern above the threshold
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2005011
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins