



AD960B

**RVK+Kaitselül. 1P+N 6kA 10A "C" 30mA -"AC"**

**Bränd:** Hager

**GTIN:** 3250611040187

RVK+Kaitselül. 1P+N 6kA 10A "C" 30mA -"AC"

**ETIM-teave:**

|                                                                   |                |
|-------------------------------------------------------------------|----------------|
| Pooluste arv (kokku)                                              | 2              |
| Kaitstud pooluste arv                                             | 1              |
| Tunnuspinge                                                       | 240 V          |
| Isolatsiooni nimipinge Ui                                         | 500 V          |
| Tunnus-impulssstaluvuspinge Uimp                                  | 4 kV           |
| Tunnusvool                                                        | 10 A           |
| Rated fault current                                               | 0.03 A         |
| Leakage current type                                              | AC             |
| Current limiting class                                            | 3              |
| Rated short-circuit breaking capacity according to IEC 60947-2    | 6 kA           |
| Rated short-circuit breaking capacity Icn according to EN 61009-1 | 6 kA           |
| Disconnection characteristic                                      | Undelayed      |
| Surge current capacity                                            | 0.25 kA        |
| Pinge liik                                                        | AC             |
| Frequency                                                         | 50 Hz          |
| Vabasti tunnusjoon                                                | C              |
| Concurrently switching neutral conductor                          | Yes            |
| With interlocking device                                          | No             |
| Over voltage category                                             | 3              |
| Pollution degree                                                  | 2              |
| Ambient temperature during operating                              | -25 °C - 40 °C |
| Width in number of modular spacings                               | 2              |
| Sisseehitussügavus                                                | 68 mm          |
| Flush-mounted installation                                        | Jah            |
| Anti-nuisance tripping version                                    | No             |
| Degree of protection (IP)                                         | IP20           |
| Connectable conductor cross section solid-core                    | 1 mm² - 25 mm² |
| Connectable conductor cross section multi-wired                   | 1 mm² - 16 mm² |

**Kinnitused / märgistused:**

