



CF464J

**Rikkevoolukaitse 4P, 63A, 300mA, AC**

**Bränd:** Hager

**GTIN:** 3250611616511

Rikkevoolukaitse 4P, 63A, 300mA, AC

**ETIM-teave:**

|                                                 |                |
|-------------------------------------------------|----------------|
| Number of poles                                 | 4              |
| Tunnuspinge                                     | 400 V          |
| Tunnusvool                                      | 63 A           |
| Rated fault current                             | 0.3 A          |
| Isolatsiooni nimipinge Ui                       | 500 V          |
| Tunnus-impulssaluvuspinge Uimp                  | 4 kV           |
| Mounting method                                 | DIN rail       |
| Leakage current type                            | AC             |
| Selective protection                            | No             |
| Short-time delayed tripping                     | No             |
| Short-circuit breaking capacity (Icw)           | 6 kA           |
| Surge current capacity                          | 0.25 kA        |
| Pinge liik                                      | AC             |
| With interlocking device                        | Yes            |
| Frequency                                       | 50 Hz          |
| Additional equipment possible                   | Yes            |
| Degree of protection (IP)                       | IP20           |
| Width in number of modular spacings             | 4              |
| Sisseehitussügavus                              | 70 mm          |
| Ambient temperature during operating            | -25 °C - 40 °C |
| Pollution degree                                | 2              |
| Connectable conductor cross section multi-wired | 1 mm² - 16 mm² |
| Connectable conductor cross section solid-core  | 1 mm² - 25 mm² |
| Explosion-proof                                 | No             |

**Kinnitused / märgistused:**

