



EMN001

**Viitelüliti 16A, 230V, 30s kuni 10min (trepikoja)**

**Bränd:** Hager

**GTIN:** 3250612339969

Viitelüliti 16A, 230V, 30s kuni 10min (trepikoja)

**ETIM-teave:**

Function	Electronic
Mounting method	DIN rail
Width in number of modular spacings	1
Sisesehitussügavus	64 mm
Number of contacts as normally open contact	1
Number of contacts as normally closed contact	0
Number of contacts as change-over contact	0
Control voltage 1	230 V - 230 V
Type of control voltage 1	AC
Frequency control voltage 1	50 Hz - 60 Hz
Control voltage 2	230 V - 230 V
Type of control voltage 2	AC
Frequency control voltage 2	50 Hz - 60 Hz
Rated switch current	16 A
Max. switching current (cos phi = 0.6)	16 A
Release-delay	0.5 min - 10 min
Push button glow-lamp current	100 mA
Wiring system	3 and 4 wire configuration
Pre-warning of switching-off	None
Current surge function selectable	No
Repetitive	Repetitive
Supply voltage	230 V - 230 V
Voltage type of supply voltage	AC
Max. incandescent lamp load	2300 W
Max. load fluorescent lamp	3600 VA
Max. load fluorescent lamp (Duo circuit)	1000 VA
Max. load fluorescent lamp (parallel compensated)	1000 VA
Max lülitusvõimsuse LED	400 W

**Kinnitused / märgistused:**

