



HA306

Koormuslüliti 3P, 125A, moodul.

Bränd: Hager

GTIN: 3250613113063

Koormuslüliti 3P, 125A, moodul.

ETIM-teave:

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	No
Number of switches	1
Max. rated operation voltage Ue AC	415 V
Rated operating voltage	380 V - 415 V
Rated permanent current Iu	125 A
Rated permanent current at AC-23, 400 V	63 A
Rated permanent current at AC-21, 400 V	125 A
Rated short-time withstand current Icw	2.5 kA
Rated operation power at AC-23, 400 V	28 kW
Switching power at 400 V	82 kW
Conditioned rated short-circuit current Iq	50 kA
Number of poles	3
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	Yes
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Suitable for intermediate mounting	No
Colour control element	Black
Type of control element	Short thumb-grip
Interlockable	Yes
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP20
Degree of protection (NEMA)	Other

Kinnitused / märgistused:

