



HCA160H

### Koormuslüliti 3P x160, 160A, 18kA, AC22A/AC23A

**Bränd:** Hager

**GTIN:** 3250613136659

Koormuslüliti 3P x160, 160A, 18kA, AC22A/AC23A

#### ETIM-teave:

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	No
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Max. rated operation voltage Ue AC	690 V
Rated operating voltage	220 V - 690 V
Rated permanent current Iu	160 A
Rated permanent current at AC-23, 400 V	160 A
Rated permanent current at AC-21, 400 V	160 A
Rated short-time withstand current Icw	2 kA
Rated operation power at AC-23, 400 V	163 kW
Number of poles	3
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	Yes
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	Yes
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Suitable for intermediate mounting	No
Colour control element	Grey
Interlockable	Yes
With pre-assembled cabling	No
Degree of protection (IP), front side	IP40
Width	75 mm
Height	130 mm
Depth	96 mm

#### Kinnitused / märgistused:

