



HHA160H

Kaitselüliti 3P x160, 100-125-160A, 25kA, reguleeritav (400/415V AC)

Bränd: Hager

GTIN: 3250613130510

Kaitselüliti 3P x160, 100-125-160A, 25kA, reguleeritav (400/415V AC)

ETIM-teave:

Rated permanent current I _n	160 A
Rated voltage	220 V - 415 V
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	25 kA
Overload release current setting	100 A - 160 A
Adjustment range short-term delayed short-circuit release	0 A - 0 A
Adjustment range undelayed short-circuit release	1600 A - 1600 A
Device construction	Built-in device fixed built-in technique
Integrated earth fault protection	No
Type of electrical connection of main circuit	Screw connection
Suitable for DIN rail (top hat rail) mounting	Yes
DIN rail (top hat rail) mounting optional	No
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
With switched-off indicator	No
With integrated under voltage release	No
Number of poles	3
Position of connection for main current circuit	Front side
Type of control element	Toggle
Complete device with protection unit	Yes
Motor drive integrated	No
Motor drive optional	No
Degree of protection (IP)	IP40

Kinnitused / märgistused:

