

Technical data sheet

Article number:  
710-00108

HTAPE-FLEX15-15x10

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| Product Group         | Vinyl Electrical Tapes –<br>Commercial Grade Vinyl Electrical Tape |
| Product Family        | HelaTape Flex 15                                                   |
| Material              | Polyvinylchloride (PVC)                                            |
| Colour                | Grey (GY)                                                          |
| Adhesion to Backing   | 2.0 N/10 mm                                                        |
| Adhesion to Steel     | 2.2 N/10 mm                                                        |
| Breaking Strength     | 28 N/10 mm                                                         |
| Dielectric Breakdown  | 6.75 kV                                                            |
| Dielectric Strength   | 45 kV/mm                                                           |
| Elongation at break   | 200 %                                                              |
| Length (L)            | 10 m                                                               |
| Operating Temperature | -10 °C to +90 °C                                                   |
| Shelf Life            | 5 years                                                            |
| Specifications        | VDE   IEC 60454-3-1-6/F-PVCP/90                                    |
| Storage Temperature   | +23 °C                                                             |
| Tensile Strength      | 19.5 N/mm <sup>2</sup>                                             |
| Thickness (T)         | 0.15 mm                                                            |
| Width (W)             | 15 mm                                                              |

