

Product Datasheet

Characteristic

IMT47218

Mureva lights, Floodlight 30W 4000K,
IP44 IR Sensor 230V



Main

Range	Mureva
Range of product	Mureva lights
product or component type	Floodlight
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
operational power in W	30 W
Light source	LED
[Ue] rated operational voltage	230 V AC
power factor	0.9
Colour rendering index	R _a ≥80
Luminous flux	3000 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour tint	Black
Provided equipment	Sensor
Electrical insulation class	Class F
Beam angle	110 °
Shape	Rectangular
Height	189.4 mm
Width	201.4 mm
Depth	26.5 mm
net weight	820 g

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP44

IK degree of protection	IK04
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.8 cm
Package 1 Width	21.8 cm
Package 1 Length	21.8 cm
Package 1 Weight	800 g
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	8.703 kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	75 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	81.624 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP1910004EN
Circularity Profile	ENVEOLI1910004EN
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins