Product Datasheet

Characteristic

MTN2300-6035

Socket-outlet, Merten System Design,
2P + E, 16A, Schuko, shutter, screwless
terminals, matt, lotus white

_____

Main

Range	Merten
Product name	System Design
product or component type	Socket-outlet
device presentation	Mechanism with fixing frame and central plate

Complementary

device mounting	Flush
Fixing mode	By screws and claws
Device application	Power supply
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	CEE 7/3
outlet standard	Schuko
Cover type	With shutter
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Colour tint	Lotus white
Material	Thermoplastic
Surface finish	Matt
Connections - terminals	Screwless terminals
IP degree of protection	IP20
Width	71 mm
Height	71 mm
Depth	40 mm
Standards	DIN 49440

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.300 cm
Package 1 Width	7.100 cm

Package 1 Length	7.200 cm
Package 1 Weight	80.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.400 cm
Package 2 Width	18.200 cm
Package 2 Length	27.400 cm
Package 2 Weight	918.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	40
Package 3 Height	19.800 cm
Package 3 Width	30.500 cm
Package 3 Length	40.300 cm
Package 3 Weight	4.040 kg

Offer Sustainability

Cradle to Cradle	Silver
REACh Regulation	Free of Substances of Very High Concern above the threshold
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes