

# Product Datasheet

## Characteristic

# MUR39911

Mureva Styl - surface mounted box - 1 gang - white



## Main

Range of product	Mureva Styl
product or component type	Mounting box
Range compatibility	Mureva Styl enclosure
Colour tint	White (RAL 9003)

## Complementary

device mounting	Surface
Number of gangs	1 gang
Cable entry	Easy valve access
Condition of use	Indoor/outdoor
Material	SEBS PP (polypropylene)
Length	76 mm
Height	54 mm
Width	76 mm
Depth	54 mm
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

Quality labels	AENOR NF
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.400 cm
Package 1 Width	7.600 cm
Package 1 Length	7.600 cm
Package 1 Weight	70.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.000 cm
Package 2 Width	17.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	800.000 g
Unit Type of Package 3	S04
Number of Units in Package 3	60
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	5.625 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP111157EN_V0
Circularity Profile	N/A