



NCN120

**Kaitselüliti 1P 10kA C-20A, 1 mod.**

**Bränd:** Hager

**GTIN:** 3250614614637

Kaitselüliti 1P 10kA C-20A, 1 mod.

**ETIM-teave:**

Sissehitussügavus	70 mm
Vabasti tunnusjoon	C
Pooluste arv (kokku)	1
Kaitstud pooluste arv	1
Tunnusvool	20 A
Tunnuspinge	400 V
Isolatsiooni nimipinge $U_i$	500 V
Tunnus-impulssaluvuspinge $U_{imp}$	6 kV
Lühisvoolu tunnuslahutusvõime $I_{cn}$ standardi EN 60898 järgi pingel 230 V	10 kA
Pinge liik	AC
Lühisvoolu tunnuslahutusvõime $I_{cu}$ standardi EN 60947-2 järgi pingel 230 V	15 kA
Frequency	50 Hz - 60 Hz
Current limiting class	3
Flush-mounted installation	Jah
Concurrently switching neutral conductor	No
Over voltage category	3
Pollution degree	2
Additional equipment possible	Yes
Width in number of modular spacings	1
Degree of protection (IP)	IP20
Ambient temperature during operating	-25 °C - 70 °C
Connectable conductor cross section multi-wired	1 mm <sup>2</sup> - 25 mm <sup>2</sup>
Connectable conductor cross section solid-core	1 mm <sup>2</sup> - 35 mm <sup>2</sup>
Explosion-proof	No

**Kinnitused / märgistused:**

