



# NEXT 0 LED 3500 HF 740 ASY

A floodlight series for indoor and outdoor use. Manufactured with luminaire housing in die-cast aluminium with polyester powder coated paint finish. Supplied with tempered safety glass cover with silicone gasket. The mounting bracket is produced in galvanized and painted steel.

Item No.	514034117
GTIN	8019455341172
Stock status code	A



## Technical specifications

### General

Product shape	Square
---------------	--------

### Technical Data

Minimum TA (°C)	-30
Maximum TA (°C)	35
IK classification	09
IP classification	66
Corrosion class	C5

### Light Technical Data

Light source	LED
Lumen Out (lm)	3301
Lumen Per Watt (lm/W)	103
Lamp colour temp (K)	4000
Colour Rendering Index	70
MacAdam step	3
Energy Class Light Source	C

### Driver / Ballast

Type of LED Driver	HF: Non dimmable
Number of Driver	1

### Lifetime

LED Lifetime L90B50 Ta25 (h)	100 000
LED Lifetime L80B50 Max Ta (h)	100 000

### Electrical Data

Main Feed AC (V) Min	220
Main Feed AC (V) Max	240
Main Feed Frequency Min	50
Main Feed Frequency Max	60
Main Feed DC (V) Min	180
Main Feed DC (V) Max	270
Total Consumption (W)	32
Protection Against Surges	4
Number Of Luminaire MCB 10B	31
Number Of Luminaire MCB 10C	53
Number Of Luminaire MCB 16B	50
Number Of Luminaire MCB 16C	85

### Optic

Optic Name	ASY - Asymmetric
Diffuser Material	Tempered glass
Diffuser Material Design	Clear

### Housing

Body Material	Aluminium
Body Colour	Grey
Main Body Colour Name	Silver grey

### Dimensions

Length (mm)	183
Width (mm)	234
Height (mm)	60
Item Net Weight (kg)	1.7664

### Cable

Cable Cross section (mm <sup>2</sup> )	1.5
Cable End / Plug Name	Open End
Cable Length (m)	1
Cable Material	RUBBER
No of Leads	3

### Mounting

Product Mounting	Pole, Wall surface
------------------	--------------------

### Logistic Data

Item Gross Weight (kg)	1.92
------------------------	------

## Illustrations

