Product Datasheet

Characteristic

NSYS3D4625T

Wall mounted steel enclosure, PanelSeT S3D, transparent door, without mounting plate, 400x600x250mm, IP66, IK08





Main

D	Day 10-T	
Range	PanelSeT	
Product name	PanelSeT S3D	
Device application	Multi-purpose	
product or component type	Compact enclosure	
Enclosure nominal height	400 mm	
Enclosure nominal width	600 mm	
Enclosure nominal depth	250 mm	
Door type	Glazed	
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 door 1 lock 1 cable gland plate	

Complementary

Variant particularity	Single piece body
,	Gutter-shaped front rail double sheet thickness
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
lock type	3 points lock, 3 mm double-bar
accessibility for operation	Front
Removable parts	Door by hinges
	Cable gland plate by screws
Material	Body: steel
	Door: steel and security glass
Surface finish	Epoxy-polyester powder
Colour	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	UL
	GL

	BV
	BV cUL DNV
net weight	11.82 kg

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.5 cm
Package 1 Width	41.5 cm
Package 1 Length	61.5 cm
Package 1 Weight	11.656 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	27
Package 2 Height	200 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	328 kg

Offer Sustainability

Green Premium product
Reference contains Substances of Very High Concern above the threshold
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
Product out of China RoHS scope. Substance declaration for your information
Yes
ENVPEP100104EN
N/A