# **Product Datasheet**

## Characteristic

# **R9XFH112**

Resi9 - comb busbar - 1L - 18 mm pitch - 12 modules - 63 A





#### Main

Range	Resi9
product or component type	Comb busbar
mounting mode	Horizontal
Accessory / separate part categor	Connection accessory
Lines description	1L
Total number of 18 mm modules	12

### Complementary

Number of ways	12 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Fork
Distance between way	18 mm
Marking	L
Insulation	Insulated
device presentation	Cuttable
[le] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	500 V AC
Mounting location	Bottom on biconnect
9 mm pitches	24
Width	220 mm
Colour	White (RAL 9003)
Range compatibility	Acti 9 Acti9 K60 Resi9 Resi9 MCB Resi9 Resi9 RCBO Resi9 Resi9 RCCB Resi9 Resi9 SWITCH

### Environment

Standards	IEC 60947-7-1 IEC 61439-2
Product certifications	CE

Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3

## Packing Units

PCE
1
1.500 cm
1.500 cm
21.200 cm
43.000 g
BB1
10
5.800 cm
8.500 cm
25.000 cm
500.000 g
S02
80
15.000 cm
30.000 cm
40.000 cm
4.320 kg

## Offer Sustainability

· · · · · · · · · · · · · · · · · · ·	
Sustainable offer status	Green Premium product
REACh Regulation	Free of Substances of Very High Concern above the threshold
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2005011
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins