

Heat shrink breakout SBO4.1



The cable breakouts are used to protect the terminated cable ends against moisture and dirt. The breakouts are suitable for both plastic and belted paper insulated 1 kV cables. They are UV resistant and halogen free and with adhesive. The colour is black.

Code	SBO4.1
GTIN	6418677442933
Name	Heat shrink breakout 0,6/1 (1,2) kV 4 core 48/14-4x15/3,2 mm

Technical specifications

Cable

Number of cores	4
-----------------	---

Dimensions

Weight	0.026 kg
Height	50 mm
Width	50 mm
Length	105 mm
Conductor size	4x6-50
Final wall thickness	1.5 mm

ETIM

ETIM Class	EC002464
Type	Heat-shrink
Model	For 4-core cables
Nominal cross section	6 ... 50 mm ²
Diameter shaft before shrink	48 mm
Diameter shaft after shrink	14 mm
Total length after shrink	105 mm
Inner diameter finger before shrink	14 mm
Inner diameter finger after shrink	4 mm

Packaging

Plastic bag

Size	10 pce
Depth	350 mm
Height	10 mm
Width	230 mm
Weight	0.269 kg
Volume	0.805 l

Carton

Size	100 pce
Depth	403 mm
Height	246 mm
Width	298 mm
Weight	3.019 kg
Volume	29.543124 l

Pallet package

Size	3200 pce
Depth	1200 mm
Height	1130 mm
Width	800 mm
Weight	116.608 kg
Volume	1084.8 l