

# Product Datasheet

## Characteristic

# SDD113106

Switch, Sedna Design & Elements, 2-way, 10AX, PRO, aluminium



### Main

|                                |                             |
|--------------------------------|-----------------------------|
| Range                          | Sedna                       |
| product or component type      | Switch                      |
| device presentation            | Mechanism with fixing frame |
| Device application             | Control switch              |
| Number of rocker               | 1                           |
| Switch function                | 2-way                       |
| Rated current                  | 10 AX                       |
| [Ue] rated operational voltage | 250 V                       |
| Network type                   | AC                          |
| Network frequency              | 50 Hz                       |
| Colour tint                    | Aluminium (RAL 7047)        |

### Complementary

|                         |                                                                                        |
|-------------------------|----------------------------------------------------------------------------------------|
| Technology type         | Electromechanical                                                                      |
| device mounting         | Flush                                                                                  |
| Actuator                | Rocker                                                                                 |
| Load type               | 1 lamp integrated ballast (100 W)                                                      |
| Surface finish          | Matt                                                                                   |
| Material                | Thermoplastic ABS-UV stabilised                                                        |
| Connections - terminals | Screwless terminals                                                                    |
| Surface treatment       | Painted                                                                                |
| Power range             | 2300 W                                                                                 |
| cable cross section     | 1.5...2.5 mm²                                                                          |
| Cable stiffness         | Rigid<br>Stranded<br>Flexible                                                          |
| Wire stripping length   | 13 mm                                                                                  |
| IK degree of protection | IK02                                                                                   |
| Fixing mode             | Claws, span of claws working range: 46...60 mm<br>Screws, span of claws working range: |
| Height                  | 73 mm                                                                                  |
| Width                   | 73 mm                                                                                  |
| Depth                   | 37 mm                                                                                  |

|                  |                                |
|------------------|--------------------------------|
| Projecting depth | 24 mm                          |
| net weight       | 0.058 kg                       |
| Targeted channel | Professional<br>Do it yourself |

## Environment

|                         |             |
|-------------------------|-------------|
| IP degree of protection | IP20        |
| Quality labels          | CE          |
| Product certifications  | EAC         |
| Standards               | IEC 60669-1 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 4.000 cm  |
| Package 1 Width              | 7.500 cm  |
| Package 1 Length             | 7.500 cm  |
| Package 1 Weight             | 61.000 g  |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 9.500 cm  |
| Package 2 Width              | 19.000 cm |
| Package 2 Length             | 27.500 cm |
| Package 2 Weight             | 698.000 g |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 120       |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 40.000 cm |
| Package 3 Length             | 60.000 cm |
| Package 3 Weight             | 9.040 kg  |

## Offer Sustainability

|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                   |
| REACH Regulation           | Free of Substances of Very High Concern above the threshold             |
| REACH free of SVHC         | Yes                                                                     |
| EU RoHS Directive          | Compliant                                                               |
| Toxic heavy metal free     | Yes                                                                     |
| Mercury free               | Yes                                                                     |
| China RoHS Regulation      | &nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes                                                                     |
| Environmental Disclosure   | ENVPEP1704002EN                                                         |
| Circularity Profile        | N/A                                                                     |