



Main

Range	Sedna
product or component type	Switch
device presentation	Mechanism with fixing frame
Device application	Control switch
Number of rocker	1
Switch function	2-way
Rated current	10 AX
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50 Hz
Colour tint	Anthracite (RAL 7021)

Complementary

Technology type	Electromechanical
device mounting	Flush
Actuator	Rocker
Load type	1 lamp integrated ballast (100 W)
Surface finish	Matt
Material	Thermoplastic ABS-UV stabilised
Connections - terminals	Screwless terminals
Surface treatment	Painted
Power range	2300 W
cable cross section	1.5...2.5 mm²
Cable stiffness	Rigid Stranded Flexible
Wire stripping length	13 mm
IK degree of protection	IK02
Fixing mode	Claws, span of claws working range: 46...60 mm Screws, span of claws working range:
Height	73 mm
Width	73 mm
Depth	37 mm

Projecting depth	24 mm
net weight	0.058 kg
Targeted channel	Professional Do it yourself

Environment

IP degree of protection	IP20
Quality labels	CE
Product certifications	EAC
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	7.0 cm
Package 1 Length	7.0 cm
Package 1 Weight	62.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	699.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	9.057 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP1704002EN
Circularity Profile	N/A