Specifications



Easy9 - flush enclosure 24 modules - plain door - with E/N term.blocks

EZ9E212P2F

() Discontinued on: 22 Jul 2022

Main

Range	Easy9	
Product or component type	Enclosure	
Enclosure type	Modular enclosure	
Nb of 18 mm modules per row	12	

Complementary

Complementary		
Enclosure mounting	Flush	
9 mm pitches	24	
Total number of 18 mm modules	24	
Type of rail	DIN	
Type of installation	Indoor	
Terminal block function	Earth / neutral	
Number of terminal blocks	2 earth / neutral (screwed) with 17 outgoers	
Cable entry	Tube entry	
Type of door	Plain door	
Door opening side	Reversible (180 °)	
[In] rated current	63 A	
[Ue] rated operational voltage	400 V AC	
[Uimp] rated impulse withstand voltage	2.5 kV	
[Ui] rated insulation voltage	500 V	
Enclosure material	Enclosure: self-extinguishing plastic	
Height	Outside: 345 mm	
Depth	Outside : 100 mm	
Width	Outside: 300 mm	
Product weight	1380 g	
Colour	White (RAL 9003)	

Environment

Standards	IEC 60670-1-24	
IP degree of protection	IP40 conforming to IEC 60529 (closed door) IP30 conforming to IEC 60529 (open door)	

IK degree of protection	IK07 conforming to IEC 62262	
pollution degree	2	
Fire resistance	650 °C (1800 s) conforming to IEC 60695-2-10	
Ambient air temperature for operation	-560 °C	
Ambient air temperature for storage	-1570 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10 cm
Package 1 Width	30 cm
Package 1 Length	34.5 cm
Package 1 Weight	1.269 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Better

Packaging made with recycled cardboard	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free product