

Technical data sheet

Article number:

111-04889 T50R

| <u>.</u> | L | |
|----------|---|----|
| | | IW |

| Product Group | Cable Ties for outdoor use (UV-resistant) |
|----------------|---|
| Product Family | T-Series in PA66W black |
| Material | Polyamide 6.6, UV-resistant (PA66W) |
| Colour | Black (BK) |

| Application Tool | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
|------------------------------|--|
| Bundle Diameter max (metric) | 50.0 mm |
| Bundle Ø min. | 1.5 mm |
| Flammability | UL 94 V2 |
| Halogen-free | Yes |
| Length (L) | 200 mm |
| Min.Tensile Strength | 225 N |
| Operating Temperature | -40 °C to +85 °C, (+105 °C, 500 h) |
| Releasable Closure (Yes/No) | No |
| Specifications | DNV IEC 62275:2006 |
| Thickness (T) | 1.2 mm |
| Toothing (Serration) | Inside Serrated |
| Variant | Inside Serrated |
| Weight/Unit | 0.0013 kg |
| Width (W) | 4.6 mm |

