

Product Datasheet

Characteristic

WDE002076

Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, with shutter, screwless terminals white



Main

Range	Exxact
product or component type	Socket-outlet
Aesthetic name	Primo
Device application	Power supply
device presentation	Complete product
Socket number	1
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Colour tint	White (RAL 9003)
Quantity per set	Set of 10

Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	With shutter
Fixing mode	By screws
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	ASA + PC
Depth	39.8 mm
Embedding depth	28 mm
Height	87 mm
Width	87 mm
Projecting depth	11.8 mm

Environment

IP degree of protection	IP20
-------------------------	------

Standards	IEC 60884-1 SFS 5610:2004 DIN VDE 0620-1 SS 4280834
Product certifications	SEMKO FIMKO NEMKO

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.900 cm
Package 1 Width	7.200 cm
Package 1 Length	7.100 cm
Package 1 Weight	72.000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP101004EN
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins