

# Product Datasheet

## Characteristic

WDE002077

Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, with shutter,white



### Main

Range	Exxact
product or component type	Socket-outlet
Aesthetic name	Primo
Device application	Power supply
device presentation	Complete product
Socket number	1
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Colour tint	White (RAL 9003)
Quantity per set	Set of 10

### Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	With shutter
Fixing mode	By screws
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm² for solid cable(s) 1 x 1.5...2 x 2.5 mm² for solid stranded cable(s)
Material	ASA + PC
Depth	39.8 mm
Embedding depth	28 mm
Height	87 mm
Width	87 mm
Projecting depth	11.8 mm

### Environment

IP degree of protection	IP20
-------------------------	------

Standards	SS 4280834 DIN VDE 0620-1 IEC 60884-1 SFS 5610:2004
Product certifications	NEMKO SEMKO FIMKO

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	8.700 cm
Package 1 Length	8.700 cm
Package 1 Weight	101.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.100 cm
Package 2 Width	18.100 cm
Package 2 Length	27.100 cm
Package 2 Weight	1.128 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	&nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP101004EN
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins