

# Product Datasheet

## Characteristic

WDE002257

Exxact call system package w/o transformer white



### Main

product or component type	Call system package
Quantity per set	Set of 1

### Complementary

wiring device mounting	Flush
Rated current	80 mA - 12 V +/- 10 % AC/DC operation 15 mA - 12 V +/- 10 % AC/DC stand by
Output voltage	<= 20 V DC <= 25 mA for LED <= 20 V DC <= 40 mA for buzzer
Colour tint	White (RAL 9003)
Local signalling	Red LED
Connections - terminals	Screw terminals
Shape of screw head	Track version
Sound frequency	3.1 kHz +/- 0.8 kHz
Acoustic level	80 dB at 1 m
Material	ABS (acrylonitrile butadiene-styrene)

### Environment

IP degree of protection	IP20
-------------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.800 cm
Package 1 Width	7.800 cm
Package 1 Length	17.400 cm
Package 1 Weight	228.000 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold

REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP101203EN
Circularity Profile	N/A