

# Product Datasheet

## Characteristic

WDE002592

2 Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, with shutter, screwless terminals, IP44 white



### Main

Range	Exxact
product or component type	Socket-outlet
Device application	Power supply
device presentation	Complete product
Socket number	2
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Provided equipment	Sealing kit
Colour tint	White (RAL 9003)
Quantity per set	Set of 5

### Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	With shutter
Fixing mode	By claw kit
Connections - terminals	Screwless terminals
Number of loop terminals	2
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC (polycarbonate) PC
Depth	25.0 mm
Height	100 mm
Width	82 mm
Projecting depth	25 mm

### Environment

IP degree of protection	IP44
Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004
Product certifications	FIMKO SEMKO NEMKO

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 cm
Package 1 Width	8.100 cm
Package 1 Length	9.900 cm
Package 1 Weight	112.000 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	&nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2306012EN
Circularity Profile	N/A