

Product Datasheet

Characteristic

WDE002596

2 Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, with shutter, screwless terminals white



Main

Range	Exxact
product or component type	Socket-outlet
Device application	Power supply
device presentation	Complete product
Socket number	2
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Colour tint	White (RAL 9003)
Quantity per set	Set of 10

Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	With shutter
Fixing mode	By claw kit
Connections - terminals	Screwless terminals
Number of loop terminals	2
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC PC (polycarbonate)
Depth	44.2 mm
Embedding depth	22.4 mm
Height	100 mm
Width	85 mm
Projecting depth	21.8 mm

Environment

IP degree of protection	IP20
Standards	DIN VDE 0620-1 SFS 5610:2004 SS 4280834 IEC 60884-1
Product certifications	SEMKO FIMKO NEMKO

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.300 cm
Package 1 Width	8.700 cm
Package 1 Length	10.100 cm
Package 1 Weight	106.000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2306012EN
Circularity Profile	N/A