# **Product Datasheet**

# Characteristic

# WDE006817

# Renova rocker switch 2 circuits 16 A 250 V white





#### Main

Range	Renova	
product or component type	Switch	
Device application	Light control	
device presentation	Complete product	
Colour tint	White (RAL 9010)	
Switch function	1-pole 2-way	

## Complementary

Technology type	Electromechanical
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screw terminals
Number of loop terminals	2
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.52 x 2.5 mm² for solid cable(s) 1 x 1.52 x 2.5 mm² for solid stranded cable(s)
device mounting	Flush
Number of rocker	2
Switch pattern	[5]
Actuator	Rocker
Material	PC/ABS
Fixing mode	By claws: insert By screws: rocker
Diameter	83 mm
Embedding depth	18 mm
Projecting depth	19 mm
IP degree of protection	IP20
Product certifications	SEMKO FIMKO CE NEMKO
Standards	EN 60669-1

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Number of Offics in Fackage 1	·
Package 1 Height	8.3 cm
Package 1 Width	8.3 cm
Package 1 Length	1.8 cm
Package 1 Weight	67.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	12.2 cm
Package 2 Width	19.4 cm
Package 2 Length	26 cm
Package 2 Weight	436 g
Unit Type of Package 3	CAR
Number of Units in Package 3	20
Package 3 Height	25 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	2.029 kg

## Offer Sustainability

•		
Sustainable offer status	Green Premium product	
REACh Regulation	Free of Substances of Very High Concern above the threshold	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	Pro-active China RoHS declaration (out of China RoHS legal scope)	
RoHS exemption information	Yes	
Environmental Disclosure	ENVPEP1507001	
Circularity Profile	N/A	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	