

Product Datasheet

Characteristic

WDE008248

Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, lid, with shutter, screw, IP44 white



Main

Range	Exxact
product or component type	Socket-outlet
Device application	Power supply
device presentation	Complete product
Socket number	1
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Colour tint	White (RAL 9003)

Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	Lid With shutter
Fixing mode	By screws
Connections - terminals	Screw
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	ASA + PC
Depth	47.0 mm
Embedding depth	28 mm
Height	87 mm
Width	87 mm
Projecting depth	19 mm

Environment

IP degree of protection	IP44
-------------------------	------

Standards	IEC 60884-1
Product certifications	SEMKO NEMKO FIMKO

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.600 cm
Package 1 Width	11.900 cm
Package 1 Length	18.300 cm
Package 1 Weight	146.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	12.800 cm
Package 2 Width	19.600 cm
Package 2 Length	26.200 cm
Package 2 Weight	816.000 g
Unit Type of Package 3	P12
Number of Units in Package 3	720
Package 3 Height	100.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	108.016 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP111036EN
Circularity Profile	N/A